

**Safety Data Sheet**  
acc. to OSHA HCS

Page 1/12

Printing date 07/07/2025  
Reviewed on 07/07/2025  
Version number: 12.06

## 1 Identification

- **Product identifier**
- **Trade name:** Petroleum Ether 40-60°C
- **Article number:** 1315
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
PANREAC QUIMICA S.L.U.  
C/Garraf 2  
Polígono Pla de la Bruguera  
E-08211 Castellar del Vallès (Barcelona)
- **Information department:** email: product.safety@panreac.com
- **Emergency telephone number:**  
+49(0)6151 93570 (Mo-Th 08:00 - 17:00 h; Fr 08:00 - 14:30 h)  
Einheitliche Notrufnummer: 112 (EU)  
Tel.: (+34) 937 489 499

Tel. (+34) 937 489 400  
Fax. (+34) 937 489 401  
e-mail: product.safety@itwreagents.com

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
Naphtha (petroleum), hydrotreated light

(Contd. on page 2)

US

Trade name: **Petroleum Ether 40-60°C**

(Contd. of page 1)

pentane

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

US

Trade name: Petroleum Ether 40-60°C

(Contd. of page 2)

· **Dangerous components:**

64742-49-0	Naphtha (petroleum), hydrotreated light	>40-≤50%
109-66-0	pentane	>20-≤50%

#### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Involve doctor immediately.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Call a doctor immediately.  
Immediately wash with water and soap and rinse thoroughly.  
Immediately remove any clothing soiled by the product.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Call a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Carbon monoxide and carbon dioxide  
Forms explosive mixtures with air at ambient temperatures.  
Vapours are heavier than air and may spread along floors.  
Beware of backfiring.  
Forms explosive mixtures with air on intense heating.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.  
Contain escaping vapours with water.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources  
Avoid substance contact.  
Do not inhale steams/aerosols.

(Contd. on page 4)

**Trade name: Petroleum Ether 40-60°C**

(Contd. of page 3)

- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Clean up affected area.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

64742-49-0	Naphtha (petroleum), hydrotreated light	1,000 mg/m <sup>3</sup>
109-66-0	pentane	3000* ppm

· **PAC-2:**

64742-49-0	Naphtha (petroleum), hydrotreated light	11,000 mg/m <sup>3</sup>
109-66-0	pentane	33000*** ppm

· **PAC-3:**

64742-49-0	Naphtha (petroleum), hydrotreated light	66,000 mg/m <sup>3</sup>
109-66-0	pentane	200000 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Away from sources of ignition and heat.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.  
Open receptacle only under localized extractor facilities.  
Store receptacle in a well ventilated area.  
Store only outside or in explosion proof rooms.  
Store under lock and key and with access restricted to technical experts or their assistants only.
- **Maximum storage temperature:** < 30°C
- **Minimum storage temperature:** 0°C

(Contd. on page 5)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 4)

- **Recommended storage temperature:** < +15°C
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 64742-49-0 Naphtha (petroleum), hydrotreated light

TLV	Long-term value: 100 ppm Skin, A3
-----	--------------------------------------

### 109-66-0 pentane

PEL	Long-term value: 2950 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 350 mg/m <sup>3</sup> , 120 ppm Ceiling limit value: 1800* mg/m <sup>3</sup> , 610* ppm *15-min
TLV	Long-term value: 2950 mg/m <sup>3</sup> , 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

### · **Exposure controls**

### · **Personal protective equipment:**

### · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

### · **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.  
Use suitable respiratory protective device only when aerosol or mist is formed.

### · **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · **For the permanent contact gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.11 mm  
Value for the permeation: Level ≥ 480 min

### · **As protection from splashes gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.11 mm

(Contd. on page 6)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 5)

Value for the permeation: Level  $\geq$  480 min

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**

Use protective suit.

Flame retardant antistatic protective clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Fluid
· <b>Color:</b>	Colorless
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value at 20 °C (68 °F):** ~7

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	40-60 °C (104-140 °F)

· **Flash point:** -21 °C (-5.8 °F)

· **Flammability:** Highly flammable.

· **Auto igniting:** 245 °C (473 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	1 Vol %
· <b>Upper:</b>	7 Vol %

· **Vapor pressure at 20 °C (68 °F):** 350 hPa (262.5 mm Hg)

· **Density at 20 °C (68 °F):** 0.65 g/cm<sup>3</sup> (5.424 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· <b>Dynamic at 20 °C (68 °F):</b>	0.25 mPas
· <b>Kinematic:</b>	Not determined.

· **Solvent content:**

· **Organic solvents:** 75-100 %

(Contd. on page 7)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 6)

<b>VOC content:</b>	75-100 % 650.0 g/l / 5.42 lb/gal
<b>Solids content:</b>	0.0 %
<b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** In the event of fire: See chapter 5

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**  
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
<b>ATE (Acute Toxicity Estimate)</b>			
Oral	LD50	>4,000-8,000 mg/kg	(rat)
Dermal	LD50	>4,000 mg/kg	(rat)
Inhalative	LC50/4 h	>22.3-28.7 mg/l	(rat)

### 64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5,000 mg/kg	(rat)
Dermal	LD50	>2,000 mg/kg	(rat)
Inhalative	LC50/4 h	>20 mg/l	(rat)

### 109-66-0 pentane

Oral	LD50	>2,000 mg/kg	(rat)
Inhalative	LC50/4 h	>25.3 mg/l	(rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

(Contd. on page 8)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Chemicals must be disposed of in compliance with the respective national regulations.  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.








**14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1268
- **UN proper shipping name**
- **DOT** Petroleum distillates, n.o.s.
- **ADR** PETROLEUM DISTILLATES, N.O.S., ENVIRONMENTALLY HAZARDOUS
- **IMDG** PETROLEUM DISTILLATES, N.O.S. (Petroleum distillates, n.o.s., PENTANES), MARINE POLLUTANT

(Contd. on page 9)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 8)

· IATA	PETROLEUM DISTILLATES, N.O.S.
· Transport hazard class(es)	
· DOT	
 	
· Class	3 Flammable liquids
· Label	3
<hr/>	
· ADR	
 	
· Class	3 (F1) Flammable liquids
· Label	3
<hr/>	
· IMDG	
 	
· Class	3 Flammable liquids
· Label	3
<hr/>	
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: Petroleum destillates, n.o.s.
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).

(Contd. on page 10)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 9)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1268 PETROLEUM DISTILLATES, N.O.S. 3, II, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Trade name: Petroleum Ether 40-60°C

(Contd. of page 10)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated light pentane

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a poison center/doctor if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Dept. Compliance

· **Contact:**

· **Date of preparation / last revision** 07/07/2025 / 12.05

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 12)

**Trade name: Petroleum Ether 40-60°C**

(Contd. of page 11)

IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flammable Liquids 2: Flammable liquids – Category 2  
Skin Irritation 2: Skin corrosion/irritation – Category 2  
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
Aspiration Hazard 1: Aspiration hazard – Category 1

· \* **Data compared to the previous version altered.**

US